

TECHNICAL DATA SHEET

ENG-SI-CLA150 SIGNATURE OAK RANGE: CLASSIC 150 BRUSHED

PRODUCT SPECIFICATIONS

PRODUCT RANGE	SIGNATURE OAK RANGE
COLOUR	CLASSIC 150 BRUSHED
PRODUCT CODE	ENG-SI-CLA150
CONSTRUCTION	MULTI-LAYERED ENGINEERED
BACKING	EUCALYPTUS
SPECIES	EUROPEAN OAK
PATTERN	1 STRIP
BOX SIZE	2.28m ²
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	10% MATTE - 9 COATS TREFFERT LACQUER
TOP LAYER	3mm EUROPEAN OAK LAMELLA
THICKNESS	14mm
WIDTH	150mm
LENGTH	1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES WITH RESTRICTIONS

WARRANTY

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P3
FORMELDELHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	4.6 kW/m ²
JANKA HARDNESS RATING	1120

