



# **TECHNICAL DATA SHEET**

# **ENG-SI-CLA190 SIGNATURE OAK RANGE: CLASSIC 190 BRUSHED**

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS				
PRODUCT RANGI	SIGNATURE OAK RANGE			
COLOUR	CLASSIC 190 BRUSHED			
PRODUCT CODE	ENG-SI-CLA190			
CONSTRUCTION	MULTI-LAYERED ENGINEERED			
BACKING	EUCALYPTUS			
SPECIES	EUROPEAN OAK			
PATTERN	1 STRIP			
BOX SIZE	2.166m <sup>2</sup>			
EDGE	BEVEL			
PROFILE	TONGUE AND GROOVE			
FINISH	10% MATTE - 9 COATS TREFFERT LACQUER			
TOP LAYER	4mm EUROPEAN OAK LAMELLA			
THICKNESS	15mm			
WIDTH	190mm			
LENGTH	1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)			



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

### **INSTALLATION METHODS**

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES WITH RESTRICTIONS

١	AI	Λ	D	Ď.	٨	N	T	7
١	IV.	H	π	ĸ	А	IV		T

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

### **AUSTRALIAN STANDARDS**

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING	P3
AS 4586-2013	F3
FORMELDELHYDE	F1
RATING	E1
CRITICAL HEAT	
FLUX (CHF) MEAN	4.6 kW/m <sup>2</sup>
AS/ISO 9239.1-2003	
JANKA HARDNESS	1120
RATING	1120







www.woodpeckerflooring.com.au Page 1 of 1