



TECHNICAL DATA SHEET

ENG-SI-SAN SIGNATURE OAK RANGE: SANDSTORM

PRODUCT SPECIFICATIONS

PRODUCT SPEC	FILICATIONS
PRODUCT RANGE	SIGNATURE OAK RANGE
COLOUR	SANDSTORM
PRODUCT CODE	ENG-SI-SAN
CONSTRUCTION	MULTI-LAYERED ENGINEERED
BACKING	EUCALYPTUS
SPECIES	EUROPEAN OAK
PATTERN	1 STRIP
BOX SIZE	2.42m ²
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	25% SATIN - 9 COATS TREFFERT LACQUER
TOP LAYER	4mm EUROPEAN OAK LAMELLA
THICKNESS	15mm
WIDTH	220mm
LENGTH	2100mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES

0	Д	K	R	A	RRAN	G	
---	---	---	---	---	------	---	--

RESIDENTIAL	LIFETIME STRUCTURAL	
COMMERCIAL	10 YEARS STRUCTURAL	

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY			
SLIP RATING	P2			
AS 4586-2013	FZ			
FORMELDELHYDE	F1			
RATING	E1			
CRITICAL HEAT				
FLUX (CHF) MEAN	4.6 kW/m ²			
AS/ISO 9239.1-2003				
JANKA HARDNESS	1120			
RATING	1120			







www.woodpeckerflooring.com.au Page 1 of 1