



TECHNICAL DATA SHEET

ENG-SI-WAL SIGNATURE OAK RANGE: WALNUT

PRODUCT SPECIFICATIONS

I NODOGI GI EC	
PRODUCT RANGE	SIGNATURE OAK RANGE
COLOUR	WALNUT
PRODUCT CODE	ENG-SI-WAL
CONSTRUCTION	MULTI-LAYERED ENGINEERED
BACKING	EUCALYPTUS / BIRCH PLYWOOD
SPECIES	EUROPEAN OAK
PATTERN	1 STRIP
BOX SIZE	2.42m ²
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	25% SATIN - 9 COATS TREFFERT LACQUER
TOP LAYER	4mm EUROPEAN OAK LAMELLA
THICKNESS	15mm
WIDTH	220mm
LENGTH	2100mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES

WADDANTY

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING	P3
AS 4586-2013	F3
FORMELDELHYDE	F1
RATING	EI
CRITICAL HEAT	
FLUX (CHF) MEAN	4.6 kW/m ²
AS/ISO 9239.1-2003	
JANKA HARDNESS	1120
RATING	1120







www.woodpeckerflooring.com.au Page 1 of 1