

TECHNICAL DATA SHEET

ENG-HA-DEL HAMPTON RANGE: DEL MAR

PRODUCT SPECIFICATIONS

| | |
|----------------------|--|
| PRODUCT RANGE | HAMPTON RANGE |
| COLOUR | DEL MAR |
| PRODUCT CODE | ENG-HA-DEL |
| CONSTRUCTION | MULTI-LAYERED ENGINEERED |
| BACKING | BIRCH PLYWOOD |
| SPECIES | EUROPEAN OAK |
| PATTERN | 1 STRIP |
| BOX SIZE | 2.888 m ² |
| EDGE | BEVEL |
| PROFILE | TONGUE AND GROOVE |
| FINISH | UV OIL |
| TOP LAYER | 2mm EUROPEAN OAK LAMELLA |
| THICKNESS | 12mm |
| WIDTH | 190mm |
| LENGTH | 1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths) |



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

| | |
|--------------------------------|-----|
| DIRECT STICK | YES |
| FLOATING ON UNDERLAY | YES |
| OVER UNDERFLOOR HEATING | YES |

WARRANTY

| | |
|--------------------|---------------------|
| RESIDENTIAL | LIFETIME STRUCTURAL |
| COMMERCIAL | 10 YEARS STRUCTURAL |

AUSTRALIAN STANDARDS

| | |
|---|-----------------------|
| ACOUSTIC RATING | DEPENDENT ON UNDERLAY |
| SLIP RATING AS 4586-2013 | P4 |
| FORMELDELHYDE RATING | E1 |
| CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003 | 3.1 kW/m ² |
| JANKA HARDNESS RATING | 1120 |