HEAD OFFICE
25 Sundercombe Street,
Osborne Park, WA, 6017
AUSTRALIA

+61 (08) 6142 1511

TECHNICAL DATA SHEET

BAM-GS-COF **GREENSHOOT SERIES: NATURAL**

PRODUCT SPECIFICATIONS

PRODUCT RANGE	GREENSHOOT SERIES
COLOUR	NATURAL
PRODUCT CODE	BAM-GS-NAT
CONSTRUCTION	SOLID COMPRESSED
BACKING	N/A
SPECIES	BAMBOO
PATTERN	1 STRIP
BOX SIZE	1.5m^2
EDGE	BEVEL
PROFILE	PATENT CLICK SYSTEM
FINISH	30% SATIN (+/- 5%) – 9 COATS TREFFERT UV LACQUER
TOP LAYER	N/A
THICKNESS	14mm
WIDTH	135mm
LENGTH	1850mm

The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	NO
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	NO

WARRANTY

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P2
FORMELDELHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	4.9 kW/m^2
JANKA HARDNESS RATING	3014