


TECHNICAL DATA SHEET

ENG-SA-OTT ESCO SERIES: OTTO

PRODUCT SPECIFICATIONS

PRODUCT RANGE	ESCO SERIES
COLOUR	OTTO
PRODUCT CODE	ENG-SA-OTT
CONSTRUCTION	MULTI-LAYERED ENGINEERED BIRCH
GRADE	SELECT
SPECIES	EUROPEAN OAK
PATTERN	1 STRIP
BOX SIZE	VARIES
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	OSMO POLYX OIL
TOP LAYER	4mm EUROPEAN OAK LAMELLA
THICKNESS	15mm
WIDTH	225mm
LENGTH	1200mm – 2400mm



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES WITH RESTRICTIONS

WARRANTY

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P3
FORMELDELHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	4.6 kW/m ²
JANKA HARDNESS RATING	1120

