

HEAD OFFICE 25 Sundercombe Street, Osborne Park, WA, 6017 AUSTRALIA

+61 (08) 6142 1511

TECHNICAL DATA SHEET ENG-SA-SON ESCO SERIES: SONOMA

The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS				
DIRECT STICK	YES			
FLOATING ON	YES			

OVER UNDERFLOOR HEATING YES WITH RESTRICTIONS

WARRANTY

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY	
SLIP RATING As 4586-2013	P3	
FORMELDELHYDE Rating	E1	
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	4.6 kW/m ²	
JANKA HARDNESS Rating	1120	



COLOUR	SONOMA
PRODUCT CODE	ENG-SA-SON

PRODUCT SPECIFICATIONS

PRODUCT RANGE

CONSTRUCTION

GRADE

SPECIES

PATTERN

BOX SIZE

EDGE	BEVEL	
PROFILE	TONGUE AND GROOVE	
FINISH	OSMO POLYX OIL	
TOP LAYER	4mm EUROPEAN OAK LAMELLA	
THICKNESS	15mm	
WIDTH	225mm	
LENGTH	1200mm – 2400mm	
	Exclusiv	

ESCO SERIES

SELECT

1 STRIP

VARIES

EUROPEAN OAK

MULTI-LAYERED ENGINEERED BIRCH