


TECHNICAL DATA SHEET

ENG-AU-SPO-130SB

SIGNATURE AUSTRALIAN RANGE: SPOTTED GUM SATIN

PRODUCT SPECIFICATIONS

PRODUCT RANGE	SIGNATURE AUSTRALIAN RANGE
COLOUR	SPOTTED GUM
PRODUCT CODE	ENG-AU-SPO-130SB
CONSTRUCTION	MULTI-LAYERED ENGINEERED
BACKING	EUCALYPTUS PLYWOOD
GRADE	STANDARD AND BETTER
PATTERN	1 STRIP
BOX SIZE	VARIABLES WITH BATCH
EDGE	BEVEL
PROFILE	TONGUE AND GROOVE
FINISH	LACQUER
TOP LAYER	3mm SPOTTED GUM LAMELLA
THICKNESS	14mm
WIDTH	130mm
LENGTH	1900mm (Product contains split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)



The photograph used in this sheet is intended as an illustration. It does not provide any indication of grading. Colours will vary between batches in stock.

INSTALLATION METHODS

DIRECT STICK	YES
FLOATING ON UNDERLAY	YES
OVER UNDERFLOOR HEATING	YES WITH LIMITATIONS

WARRANTY

RESIDENTIAL	LIFETIME STRUCTURAL
COMMERCIAL	10 YEARS STRUCTURAL

AUSTRALIAN STANDARDS

ACOUSTIC RATING	DEPENDENT ON UNDERLAY
SLIP RATING AS 4586-2013	P2
FORMELDELHYDE RATING	E1
CRITICAL HEAT FLUX (CHF) MEAN AS/ISO 9239.1-2003	3.2 kW/m ²
JANKA HARDNESS RATING	11kN

